



PINCH VOLUNTEER FIRE DEPARTMENT

P.O. BOX 477

PINCH, WV 25156-0477

WWW.PINCHFIRE.COM

RE: Two (2) Thermal Imaging Cameras

Date: April 14, 2011

Contact: Lt. Doug Beasley
Pinch Volunteer Fire Department
PO Box 477
Pinch, WV 25156
Telephone (304) 545-8129
E-Mail: dbeasley@pinchfire.com

Bid Opening: Bids must be received on or before Thursday, May 5, 2011 7:00 pm at the Pinch Volunteer Fire Department – Main Station
Physical address: 231 North Pinch Road Elkview, West Virginia 25071
Mailing Address: PO Box 477 Pinch, West Virginia 25156

Instructions to Bidders:

Please use this cover sheet for your bid

1. Bids must be received in a sealed envelope with date and time of the bid opening on the outside of the envelope. Faxed bids will NOT be accepted.
2. Bid must be F.O.B. Delivery Point, unless otherwise indicated in proposal.
3. All bids should be signed and in ink, showing all facts and the total amount of the bid.
4. The Pinch Volunteer Fire Department reserves the right to accept or reject, in part or in whole, any bid submitted, whichever is in the best interest of the Pinch Volunteer Fire Department.

Item No.	Description	Amount
1	2 Bullard Personal Issue Thermal Imaging Cameras (per the attached specifications)	
2	2 Vehicle Charging Units	
3	Provide list of options/accessories and pricing for each	

Vendor Name: _____ Date: _____

Signature: _____ Telephone: _____

Address: _____

E-mail Address: _____

SPECIFICATIONS: The following specifications are intended to describe a thermal imaging camera suitable for use in structural firefighting. The details contained in these specifications are not designed to exclude any vendor from bidding, but are offered as a means of describing the needs of the Pinch Volunteer Fire Department. All specifications are minimum requirements:

<u>Quantity</u>	<u>Item</u>	<u>Model #</u>
2	Bullard Personal Issue Thermal Imaging Cameras To meet the following specifications:	Model/Eclipse Eclipse 160

I. Warranty

The manufacturer shall warrant the thermal imager and all charging systems free of defects in material and workmanship, under normal use and service, for a period of one year effective upon initial product activation. In addition, the imager’s outer shell or housing shall carry a limited lifetime warranty.

II. Service

The manufacturer must be located in the U.S.A. and provide a full-service repair center in the U.S.A. to ensure timely and efficient processing of any service related issues concerning the imager. Warranty repairs must carry a guaranteed 48-hour turnaround (2 full business days from the time of receipt at the service center to the time that the manufacturer ships the imager. Non-warranty repairs must carry a guaranteed 48-hour (2 full business days) turnaround from the time the manufacturer receives purchase order authorization to complete the repairs to the time the manufacturer ships the imager. Upon request, the manufacturer must provide the names and contact information for three (3) fire departments that can serve as references, verifying that the manufacturer complies with this requirement.

III. Quality

The manufacturer must ensure quality, design and manufacturing methods through third-party certification to ISO 9001, or its equivalent. To ensure that the product is of the highest quality, documentation must be presented upon request illustrating a battery of tests that have been conducted to verify water resistance, heat resistance and shock/impact resistance.

IV. Physical Configuration

The imager shall be a hand-held design, having a 2.4-inch LCD viewing screen. Total weight of the imager shall not exceed 1.5 lbs. with the battery installed. The imager shall ship in a padded, re-usable delivery case. The imager shall include one rechargeable battery, a battery charger with AC adapters. The imager’s physical dimensions shall be no more than four (4) inches tall, four (4) inches wide and seven (7) inches long.

V. Durability

The imager shall remain operational after being submerged under 3 feet of water for 30 minutes. The imager shall withstand a 6-foot drop in any orientation and sustain no operational damage. The manufacturer must perform these tests in front of designated department representatives at a mutually determined time and location. Failure to perform these tests in front of designated department representatives shall constitute non-compliance with this portion of the specification.

VI. Technology

The imaging technology shall utilize a 160x120 pixel un-cooled vanadium oxide (VOx) focal plane array. To ensure reliability, the detector must be designed and manufactured by a company that has provided, for at least five (5) years, detectors used in the fire service. A detector from a company without five (5) years of experience in the fire service is not acceptable. The Noise Equivalent Temperature Difference (NETD) shall be less than 75 mK. The imager shall exhibit an ability to evade whiteout when pointed directly at flames. The detector shall operate with core temperature ranges of -20°C to 85°C (0°F to 175°F). The dynamic range of the detector and associated electronics shall be nominally 550°C (1020°F). The detector spectral response shall be 7 to 14 microns. Mid-wave or short-wave infrared products that operate below this portion of the infrared spectrum (below 7.5 microns) are not acceptable due to unreliable performance in smoky conditions.

VII. Image Colorization

In order to provide a greater degree of safety, the imager shall utilize a tri-color automatic colorization mode available as an option or upgrade. This colorization mode shall utilize a yellow/orange/red color scheme. The display will show yellow colorization at temperatures of 500 degrees F to 799 degrees F, orange colorization at temperatures of 800 degrees F to 999 degrees F, and red colorization at temperatures of 1000 degrees F or hotter. Such colorization shall be gradient in nature so as to be able to discern scene details though the color (this requirement does not apply to manually engaged colorization).

VIII. Outer Housing

The imager shall be ergonomically designed, and the outer shell or housing must be manufactured from heat-resistant Ultem® thermoplastic. Due to the likelihood of rigorous use, the Ultem must be molded with color pigment throughout to mask small surface scratches. Outer shells or housings that are painted or otherwise lack consistent color through their entire thickness are not acceptable.

IX. Colors

The imager should be available in no less than seven scratch-resistant colors to allow for color-coding as needed by the department. Colors shall include, at a minimum: Red, Yellow, Black, White, Orange, Blue, and Lime-Yellow.

X. Monitor/Screen

The imager shall have a 2.4" diagonal LED backlit Liquid Crystal Display (LCD) screen. The display shall consist of no less than 112,320 pixels for high quality resolution. The screen must be visible in thick smoke to the operator while using it at arms length. In addition, a clear polycarbonate cover must protect the display screen. This cover must be field-replaceable and watertight.

XI. Lens

The imager shall possess an f/1.25 lens fabricated of chalcogenide or germanium and have no less than a 33° x 45° field of view.

XII. Visual Indicators

The imager shall have a battery status indicator on the viewing display to reduce imager size. Battery indicators that are not located on the display, such as separate LED based indicators, are unacceptable as they increase imager size. The imager shall be capable via option or upgrade to provide, on the viewing display, surface temperature measurement of objects. The imager must be able to provide simultaneous presentation of bar graph and numeric temperature indicators as well as separate presentation of either indicator.

XIII. Switches

The imager shall use only one switch to activate the unit. The switch must be recessed and protected to avoid accidental shut-off. The switch shall be a mechanical capture switch which allows for automatic power restoration during a hot battery swap and eliminates the need for a "push and hold" mechanism for powering off that is associated with electronic switches. The imager shall incorporate a manual colorization mode as an option or upgrade. The imager must utilize a pair of switches for activating this colorization mode, which helps the user identify the hottest objects in a scene. This colorization mode must be manually adjustable by the user and colorize the hottest objects in a scene with a color that is unique to this mode. Thermal imagers that use yellow, orange, or red to identify hot objects for a manual colorization mode are not acceptable as they can easily be confused with the automatic colorizations modes which typically use such colors to designate fire and high heat conditions.

XIV. Strap Systems

To reduce bulk, the imager must not have an integral strap system; however, the imager shall accommodate an available self-retracting strap. This retractable strap shall be attachable to a D-ring at the base of the thermal imager, under the display, and must be capable of holding the unit to the firefighter's body with the full weight of the imager, with battery, hanging unsupported from the strap.

XV. Power Supply

The imager shall be provided with a rechargeable battery and battery charger. The battery shall be a 2.4-volt nickel metal hydride (NiMH) pack, providing a minimum of 3 hours of continuous use with all standard functions and

features activated. The battery must be capable of a minimum of 1,000 charges. The battery shall have an Ultem outer shell. The battery must be capable of being loaded into the housing only one way and must be inserted and removed by a person wearing standard firefighting gloves. A lithium-ion battery is an unacceptable substitute for NiMH due to lithium's higher risk of explosion when exposed to high heat.

XVI. Operation

Once the imager is registered (see section XVIII), the imager must be fully operational no more than four (4) seconds after activating the power switch. The imager must not have a standby switch or mode.

XVII. Customized Startup Graphics

The imager must be equipped with the capability of providing customized factory-loadable and user-loadable startup graphics. These graphics will be displayed on the imager's display during the startup sequence.

XVIII. Truck Mount

The manufacturer must offer a truck mounted charging system to mount the imager and internal charging system in a vehicle or fire apparatus or on the wall of a fire station. The charging system shall come standard with an additional battery, all necessary mounting hardware, a direct charge system, and a connector that enables the use of an AC/DC power supply. The system must charge the battery in the imager at the same time it charges a spare battery utilizing separate charging systems. The battery in the imager must be charged through contacts on the imager. No cables or wires connecting the imager to the charging system are acceptable, nor are straps or other connecting devices to hold the imager to the truck mounting system. The system must be compliant to NFPA 1901 when properly mounted in a vehicle or fire apparatus. The truck mount must carry a one year warranty.

XIX. Orientation

The manufacturer must make available, free of charge, an online product and application orientation program. This program shall include a rich, interactive, multimedia experience providing comprehensive product familiarization and detailed application courses. The courses will be self paced and rich in multimedia content accompanied by voice presentation of course materials. At the completion of each course, the manufacturer must provide, via the orientation program, an individualized user assessment mechanism. PowerPoint, CD, or written orientation materials are unacceptable substitutes.

XX. Registration, Service and Support

For added user security and cataloging of equipment, the manufacturer must utilize a user registration and support interface with the imager. This interface will enable the user to activate and register the imager for initial use, maintain and organize equipment inventory, download future product updates and features, and enable other service and support functions.

XXI. Security

The imager shall also be equipped with an integral security feature which saves the registered user information directly to the imager's memory in an effort to identify the rightful owner and provide for resource tracking and identification.

XXII. Delivery

The manufacturer shall deliver the thermal imager in 30 days or less after receiving a purchase order.

Total bid amount for Two (2) Thermal Imaging Cameras \$_____

The Pinch Volunteer Fire Department reserves the right to assess any substitute items for suitability when making the final decision.

All items are to be delivered to the Pinch Volunteer Fire Department.